



Threaded 2 & 3-pc - 316 Stainless Steel Ball Valves

KV-020 2 PC Full Port, 1000 WOG

PART NUMBER	SIZE / INCHES	LIST PRICE
KV-020-025	1/4	38.77
KV-020-375	3/8	38.77
KV-020-050	1/2	40.48
KV-020-075	3/4	54.23
KV-020-100	1	83.65
KV-020-125	1-1/4	112.91
KV-020-150	1-1/2	164.39
KV-020-200	2	245.00
KV-020-250	2-1/2	457.60
KV-020-300	3	655.65

KV-030-TH 3 PC Full Port, 1000 WOG

PART NUMBER	SIZE / INCHES	LIST PRICE
KV-030-025	1/4	46.86
KV-030-375	3/8	46.31
KV-030-050	1/2	50.00
KV-030-075	3/4	72.32
KV-030-100	1	105.10
KV-030-125	1-1/4	151.25
KV-030-150	1-1/2	206.36
KV-030-200	2	305.25
KV-030-250	2-1/2	611.50
KV-030-300	3	814.33

FEATURES

- Investment Castings for Body and End Cap
- Blow-out Proof Stem
- Various Thread Standards Available
- Full Port

STANDARDS

- Design: ASME B16.34, API 608
- Pipe Thread: ASME B1.20.1, BS21
DIN 2999/259, BSP
- Inspection & Testing: API 598

SPECIFICATION

- Working Pressure: 1000 psi at 100°F (38°C)
- Temperature Range: -50° to 350° F (-46° to 177° C)